




RAMSAUER®

Flex Primer

Adhesive primer for Ramoflex sealing tapes on porous surfaces

LASTING BONDS.



Technical data sheet

Version: 08-2024

1. Technical datas

Base	Solvent free polyacrylate dispersion
Colour	white
flash-off time	~30 - 60 min. (at +23°C/50% relative humidity); max. 180 min.
Viscosity	~80 mPa*s
Application temperature (substrates and primer)	Lower + 5°C, upper + 35°C
Consumption guidelines: / kg	Stone/concrete: approx. 12m ² ; sof wood fibreboard: approx. 6m ²
Container size	1kg safety can
Storage life	12 months in unopened original can

2. Properties

Flex Primer is a solvent-free adhesion-promoting primer on a polyacrylate dispersion basis, which is used primarily for treating porous, sandy or less solid substrates (bricks, concrete, wood, ceramics, etc.), painted and unpainted metals, rubber and PVC to improve the adhesion of Ramoflex Adhesive Tapes. It is easy to apply, fast curing and forms a non-gluing surface. In case of heavily contaminated substrates the primer can also be used to facilitate cleaning.

3. Processing

The recommended application temperature must be strictly adhered to. At temperatures below +5°C water will condensate on the primer which will cause a drastic reduction of adhesion of the Ramoflex Adhesive Tape to the Flex Primer coat. Stir or shake the primer well before applying. Apply the undiluted product to the cleaned and dry adherent surfaces by means of a brush or cloth. In case of problematic substrates apply several primer coats if required. Let the primer coats dry well in between. Protect primed surfaces from moisture and dust. Apply the sealant only after sufficient open time.

4. Safety instructions

Keep away from sources of ignition. Don't smoke at work. Keep out of reach of children. Request a safety data sheet! Please note the information on the current EC safety data sheet. These are available at any time on our homepage at www.ramsauer.eu.

5. Liability for defects

The information, in particular the suggestions for the processing and use of our products, is based on our knowledge and experience in normal use cases at the time of printing. Depending on the specific circumstances, in particular with regard to substrates, processing and environmental conditions, the results may differ from this information. Therefore the guarantee of a work result or a liability, for whatever legal reasons, can be justified neither from these references, nor from a verbal consultation, unless we are guilty of intent or gross negligence in this respect. Ramsauer guarantees that its products comply with the technical properties specified in the technical data sheets until the expiry date. Product users must consult the latest technical data sheet, which can be requested from us. Our current General Terms and Conditions apply, which you can download at any time from our homepage at www.ramsauer.eu. On publication of a new version/revision of the technical data sheet, all previous versions of the respective product lose their validity.